

# Dr. Fixit Torchshield Primer



## SOLVENT BASED BITUMEN PRIMER

### Description

**Dr. Fixit Torchshield Primer** is a solvent based bitumen modified primer conforming to **ASTM D/41**, to be used to seal and prepare the substrate prior to the installation of the **Dr. Fixit Torchshield** torch-on and **Dr. Fixit Samshield**, self adhesive membranes. In addition to that, it also acts as a binder for the dust particles which gets accumulated on the concrete surface even after cleaning.

### Typical Applications

Ensure that the surface to be primed is dry and free from dust, oil, paint, curing compounds and any other contaminating materials. Stir contents well before use. Apply by brush, roller. **Dr. Fixit Torchshield Primer** must be dry before applying membrane.

### Packaging

20 ltr

### Technical Information

PROPERTY	TEST	RESULT
Density.	ASTM D 70	0.8 - 1.2 g/cc
Saybolt Furol Viscosity at 25°C, Seconds	ASTM D 88	30-70
Drying Time	BS 3900	24 hours at 30°C
Tack Free Time		Max 4 Hrs at 30°C
Solubility in Trichloroethylene %	ASTM D 2042	99
Water Content, %	ASTM D 95	0.5 (max)
Flexibility	BS 3416	Pass
Flash Point	38°C	
Solid content		53-59 % ± 2%

### Theoretical Coverage

3-4 sqm /lt/coat. However, the coverage will depend on the porosity of the substrate. In order to ascertain the exact coverage, a trial application should be carried out on site.

### Limitation

**Dr. Fixit Torchshield Primer** should be used with appropriate mask and breathing apparatus in areas with poor ventilation/air flow.

### Shelf Life

Shelf life is 12 months from the date of manufacturing if stored in original and unopened packaging in a cool dry place away from direct sunlight.



## Other Products Categories available

Dr. Fixit brings you the widest range of Construction Chemicals



Pidilite Industries Limited  
Construction Chemicals Division  
Ramkrishna Mandir Road, Post Box No. 17411  
Andheri (E) Mumbai 400059 INDIA  
Tel +91-22-2835 7000 • Fax +91-22-2835 7008  
www.drfixit.co.in • info@drfixit.co.in

Dr. Fixit Advice Centre (Toll Free No.) 1800 209 5504

**DISCLAIMER** The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.