

Trusted Partners In Construction Chemicals



MCON ULTRA GYPBOND

HIGH PERFORMANCE GYPSUM BONDING AGENT

Product Description:-

MCON ULTRA GYPBOND is polymer based coarse coating to perform as a bonding agent to create strong bond of Gypsum Plaster on any cementitious substrate including high quality concrete surfaces. It comes in Green color and hence is easily traceable for application. It provides a strong chemical bonding coat and also a mechanical bonding substrate.







Trusted Partners In Construction Chemicals

Areas of Application:-

- ✓ For gypsum plaster bonding to RCC Surfaces as a bonding agent.
- **✓** For gypsum plaster bonding to plastered surfaces as a bonding agent.
- ✓ For gypsum plaster bonding on variety of surfaces like blockwork, gypsum boards, ply etc



Features & Benefits:-

- Excellent adhesion to most building substrates.
- Dual bonding (mechanical as well as chemical grip).
- The green colour makes identification easy.
- Ready to apply.
- ✓ Can be applied on any low-suction surface (concrete surfaces like RCC columns, beams, slabs, shear walls).
- ✓ Works equally well for both gypsum and sand-cement plaster.
- ✓ Twenty times faster than hacking and also more effective.



Trusted Partners In Construction Chemicals

Method Of Application:-

Surface preparation is vital for effective adhesion and bonding of ULTRA GYPBOND.

To start with, free the surface from laitance, loose dust particles, oil, grease and other dirt.

Stir constantly until all the solid contents are uniformly distributed throughout the solution of ULTRA GYPBOND and slurry of uniform consistency is achieved.

Apply this slurry on the substrate using a soft 4 - inch wide paint brush or a roller brush.

Apply the slurry in one direction only and that too in single coat.

The coating will dry in 24 hours and you can overcoat it with Gypsum plaster within 15 days from date of application of ULTRA GYPBOND.

Technical Specefication:-

Colour	Green
Form	Liquid emulsion
	qa.a ca.s.s.
Service Temp.	- 40º C to + 90º C
Sup. Curavitus	4.25 04
Sp. Gravity	1.25 ± .01
Ph	7 - 9
Bond Strength	1 Mpa at 28 days



Trusted Partners In Construction Chemicals

Coverage:-

1 kg ULTRA GYPBOND covers 45 to 50 sq.ft.



Storage and Shelf life :-

Store away from direct sunlight. 6 months from date of manufacture.



Safety Precautions:-

MCON ULTRA GYPBOND is non-toxic, non-flammable and non-hazardous. However, any splashes on any part of the human body must be washed with plenty of water.





Trusted Partners In Construction Chemicals

Packaging:-

5 Kgs, 20 Kgs



*(Mcon Rasayan has maintained the highest level of Quality and Consistency by following Systems and is certified as an ISO 9001 : 2015, ISO 14001:2015 & ISO 18001:2015 Company.)

Address: Venus Enterprises, Raj Sunderam, Shiv Vallabh Road, Near Maruti Nagar, Ashokvan, Dahisar (E), M-68

Call us: +91 9322226109/ 08657642713 / 022- 28488467

Email id: venus_enterprises04@yahoo.com

Website: www.venusentprs.com







