



MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals



MCON ELASTO COAT PRIMER

WALL PRIMER FOR ELASTO COAT

Product Description :-

MCON ELASTO COAT PRIMER is an exterior acrylic primer which is a combination of Primer and sealer, and is designed for exterior surfaces to provide best in class adhesion, resistance to alkali and primary efflorescence. MCON ELASTO COAT PRIMER It is highly user friendly and eco-friendly. MCON ELASTO COAT PRIMER has excellent bonding to most of the Cementitious surfaces, breathing properties, water resistance and excellent acceptance to next coat of Coating. MCON ELASTO COAT PRIMER provides excellent whiteness to the substrate and increases the coverage of MCON ELASTO COAT.





MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals

Direction Of Uses :-

Adequate surface preparation as given below is necessary for product performance.

Application of Primer is an ideal practice prior to MCON ELASTO COAT.

SURFACE PREPARATION

NEW MASONRY :-

MCON ELASTO COAT Elastomeric Waterproof coating should not be applied to fresh concrete and to other surfaces less than seven days old.

Ideally concrete should be allowed to cure for 28 days before application.

Power wash to ensure no under bound sand or cement remains on the surface.

Allow the surface to dry and apply MCON ELASTO COAT PRIMER one coat.

Let the primer get absorbed in the surface and apply MCON ELASTO COAT after 4 hours of primer application.

EXISTING MASONRY

Power wash to remove all loosely adhered coatings, dirt, mild dew and other contaminants.

Fill any existing cracks up to 3 mm with Crack Filler (Non Shrink Crack filler) paintable sealant. And more than 3 mm with Polymer Mortar (Ready to use Polymer Repair Mortar).



MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals

Allow the surface to dry and apply MCON ELASTO COAT PRIMER one coat. Let the primer get absorbed in the surface and apply MCON ELASTO COAT after 4 hours of primer application.



Technical Specification :-

Nature :	Acrylic co-polymer
Priming :	Priming to be done with MCON ELASTO COAT PRIMER
Drying Time :	Dry to touch – 20 minutes.
Shades :	White / Off White






MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals

Shelf Life & Storage :-

12 months in original packing if stored at room temperature i.e.25° C.




Coverage :-

70 Sqft / Ltr.



Packing :-

20 Ltr



**(Mcon Rasayan has maintained the highest level of Quality and Consistency by following Systems is certified and as an ISO 9001 : 2015, ISO 14001:2015 & ISO 18001:2015 Company.)*

Address : Venus Enterprises, Raj Sunderam , Shiv Vallabh Road, Near Maruti Nagar, Ashokvan, Dahisar (E), M-68

Call us : +91 9322226109/ 08657642713 / 022- 28488467

Email id : venus_enterprises04@yahoo.com

Website : www.venusentprs.com

