



MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals

• MCON MAGIC COAT CLEAR •

**ACRYLIC BASED TRANSPARENT
WATERPROOFING COATING**

Product Description :-

MCON MAGIC COAT CLEAR is a single component, acrylic polymers based, liquid applied transparent coating. It cures by reaction with atmospheric moisture to give a tough elastomeric waterproof membrane. MCON MAGIC COAT CLEAR is elastomeric in nature. MCON MAGIC COAT CLEAR has excellent flexibility and bonding with concrete, water resistance, crack bridging properties, weathering durability.





MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals

Advantages :-

- ✓ Cold curing, cures to a tough, flexible and abrasion resistant coating.
- ✓ Bonds strongly on cement concrete, asbestos, painted surfaces, cement plastered applied surfaces.
- ✓ High elasticity - Cures to give a permanently flexible resilient barrier for water over a wide range of temperatures.

Areas Of Application :-

- ✓ Terrace Gardens, Terraces - ON CHINA CHIPS
- ✓ Tiled surfaces of bathrooms, toilets, balconies, etc.
- ✓ Car Decks, Podiums.
- ✓ External Painted Walls of the buildings.

Typical Properties :-

Appearance	Clear
Tack Free Time @28° C	12 hours
Time to Full Cure @28° C	72 hours
Solid Content, %	55± 2
Elasticity	100%



MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals

Precautions & Limitations :-

Surface to be dry for application as the material is cured in presence of moisture.

Moisture level shall not be essentially more than 0.5%.

Soft settling is likely to be observed in containers and the same shall be stirred thoroughly and carefully to achieve a homogeneous consistency.

Avoid application on very hot substrate during a very hot and windy conditions.

Film formation may not be uniform and gradual under such circumstances & skinning on top surface may lead to formation of blisters and bubbles due to entrapped vapor from within the material.

Curing Details:

Curing Treatment: MAGIC COAT CLEAR membrane must be allowed to cure for a minimum of 72 hours @ 27° C before allowing next treatment or foot traffic. Where damage to the membrane is possible (by traffic, backfilling, etc) it should be protected by a cementitious screed or protection boards.





MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals

Packing and Coverage :-


20 liters.

As a waterproofing coating: 35 - 40 sq.ft./ liter in 2 coats



Shelf Life :-

12 months in original packing if stored at room temperature i.e.25° C



**(Mcon Rasayan has maintained the highest level of Quality and Consistency by following Systems is certified and as an ISO 9001 : 2015, ISO 14001:2015 & ISO 18001:2015 Company.)*

Address : Venus Enterprises, Raj Sunderam , Shiv Vallabh Road, Near Maruti Nagar, Ashokvan, Dahisar (E), M-68

Call us : +91 9322226109/ 08657642713 / 022- 28488467

Email id : venus_enterprises04@yahoo.com

Website : www.venusentprs.com

Follow us on :

