



MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals

● MCON READY PLASTER RENDER ●

CEMENT SAND THIN SECTION RENDER

Product Description :-

MCON Ready Plaster Render is a cement sand fiber reinforced, ready to use render for internal & external surface corrections purpose. It is convenient, easy to use, strong and binds better to its substrate. This product is composed of good quality cement, properly selected aggregates, Fibers & additives. Its well graded aggregates which are clean and silt free ensure that the plaster has a very cohesive and smooth finish. The waterproofing and bonding polymers give the plaster a better bonding with water tight characteristics. MCON Ready Plaster Render is easy to use as it can be applied with trowel.





MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals

Areas Of Application :-

- ✓ Thin Plastering on block work and concrete substrates in new construction.
- ✓ External and Internal leveling application for repair and rehabilitation works.
- ✓ Leveling of Walls prior to tiling to make good undulation upto 10 mm.



Features & Benefits :-

- ✓ Crack free & firm surface that preserves beauty of building for longer time.
- ✓ Factory made product with consistent quality.
- ✓ Very less rebound loss.
- ✓ Ready to use, only clean water to be added at site.
- ✓ Better bond than conventional cement based mortar
- ✓ Improved labour productivity hence reduces costs
- ✓ Moisture resistant - Offers excellent resistance to moisture ingress.
- ✓ Good mechanical strength



MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals

Technical Specification :-

Binder :	Grey Portland Cement 53 grade
Density :	Dry Mix - 1.6 kg/ltr Wet Mix - 1.8 kg/ltr (mixed with water)
Water Intake :	150 – 200 ml per kg (approx 8 Liters in a bag of 40 kg)
Pot Life :	75 Minutes
Thickness :	5 – 6 mm per single coat





MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals

Methods Of Application :-

Clean the substrate , free from all loose particle, oil & grease, paints or free sand.

Water jet cleaning is advisable.

Wet the surface before application of the plaster.

Mix one bag of 40 kg of Mcon Ready Plaster Render with 7 to 8 ltr of water using a mechanical mixer.

Small quantity can be mixed using a trowels and a bucket. All care should be taken that the mixing is done thoroughly.

Use the mixture within 1 ¼ hrs (75 min) after addition of water.

Curing of the plastered surface can be done after 10 – 12 hrs and should be done for 2 – 3 days.



Coverage :-

50-60 sq. ft per 40 kg bag at 5 – 6 mm thickness.






MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals


Shelf Life & Storage :-

6 months from manufacture in original unopened bags if stored in dry conditions.



Packing :-

40 kg in moisture-resistant bag.



**(Mcon Rasayan has maintained the highest level of Quality and Consistency by following Systems is certified and as an ISO 9001 : 2015, ISO 14001:2015 & ISO 18001:2015 Company.)*

Address : Gala No.6, Bardanwala Estate, Bandivali Hill Road, Jogeswari (W), Mumbai - 400102

Call us : +91 8657448832 / 022- 26790031

Email id : salesmcon16@gmail.com

Website : www.mconrasayan.com / www.mconrasayan.net

Follow us on :    