



MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals



MCON TILE GROUT EP

EPOXY TILE JOINT FILLER IN ATTRACTIVE COLORS FOR DURABLE HARDWEARING TILE JOINTS

Product Description :-

MCON TILE GROUT EP is a high performance epoxy grout that offers color uniformity, durability and stain resistance with ease of use. Used for filling tile joints of width 3 mm to 10 mm in both interior and exterior areas. MCON TILE GROUT EP is designed for use on ceramic tile, glass tile and stone applications, both residential and commercial. It can be used both interior and exterior on floors and walls. Ideal for re-grouting applications





MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals

Areas of Application :-

- ✓ Suitable for filling tile joints at 3 – 10 mm joint thickness wall and floor tiles, mosaics, vitrified and fully vitrified tiles, marble, terrazzo and natural stone.
- ✓ The set tile grout is water-resistant and is suitable for use in showers and totally immersed situations such as swimming pools.
- ✓ MCON TILE GROUT EP can be used in Residential, commercial, external facades and wet areas.

Features & Benefits :-

- ✓ Ideal for installations at wide temperature ranges.
- ✓ Uniform color — no blotchiness or shading.
- ✓ Easy to maintain, cleanable to the original color.
- ✓ Stain resistant.
- ✓ Meets performance requirements of ANSI A118.3.
- ✓ 80 minutes working time at 70°F (21°C).
- ✓ Tough, durable, and crack resistant.
- ✓ Outperforms cement based grout.
- ✓ Non-sag formula for walls and floors.





MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals

Method of Application :-

MCON TILE GROUT EP comes in two part system in the ratio of 70:30 - Part A and Part B. Mix Part A + Part B with the help of slow speed drill having paddle attachment.

Blend until a homogeneous, lump-free mixture is obtained.

Clean off surplus adhesive from the tile face and between joints.

When applying, the grout joints should be free of dirt, debris or tile spacers.

Sponge or wipe dust/dirt of tile faces and remove water standing in joints.

Pack joints full and free of voids with rubber grouting float.

Remove excess grout from tile faces using edge of rubber float and diagonal strokes (at 45° angle to direction of joints).

When the joints have set, use a moist sponge to remove excess grout from the tile and joint. Use minimal water for clean up.

Final clean up to remove any grout haze should be carried out within the next 12 – 24 hours.





MCON RASAYAN PVT. LTD.

Trusted Partners In Construction Chemicals


Packing & Coverage :-

MCON TILE GROUT EP is supplied in 1 kg box and 5 kg Bucket.

**For coverage please refer to our shade card.*

Shelf Life & Storage :-

MCON TILE GROUT EP will have a shelf life of 6 months in unopened containers when kept in dry conditions at a temperature between 5°C to 45°C. Storage at higher temperature or high humidity may reduce shelf life.



Health & Safety :-

MCON TILE GROUT EP is non-toxic. However, splashes on the skin should be washed well with water and in contact with eye occurs, wash well with water and seek medical advice.



**(Mcon Rasayan has maintained the highest level of Quality and Consistency by following Systems and is certified as an ISO 9001 : 2015, ISO 14001:2015 & ISO 18001:2015 Company.)*

Address : Gala No.6, Bardanwala Estate, Bandivali Hill Road, Jogeswari (W), Mumbai - 400102

Call us : +91 8657448832 / 022- 26790031

Email id : salesmcon16@gmail.com

Website : www.mconrasayan.com / www.mconrasayan.net

Follow us on :    